

DATE NIGHT FO-0050

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: DATE NIGHT FO-0050
UFI	: H6RX-K82E-J00C-54J3
Product code	: FO-0050
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Professional use, Industrial use
Industrial/Professional use spec	: Industrial For professional use only
Use of the substance/mixture Function or use category	: Perfumes, fragrances : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

FRAGRANCE ORCHARD

Neutrino,
Albert Road,
Essex CM7 3JQ
GB - United Kingdom

1.4. Emergency telephone

Emergency number : +44 1376 555185

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

[CLP] Hazard pictograms (CLP)



GHS07

GHS09

Signal word	: Warning
(CLP) Contains	: Iso E Super; Vertenex; Cedramber; Cyclamal; COUMARIN; Triplal (Vertocitral)

Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 - IF ON SKIN: Wash with plenty of water.
Extra phrases	: For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	26.2 – 52.3	Not classified
Iso E Super	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989- 04	7.9 – 15.8	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Vertenex	CAS-No.: 32210-23-4 EC-No.: 250-954-9 REACH-no: 01-2119976286- 24	4 – 8	Skin Sens. 1B, H317
Stemone	CAS-No.: 22457-23-4 EC-No.: 245-010-8	2.8 – 5.6028	Aquatic Chronic 3, H412
GAMMA-OCTALACTONE	CAS-No.: 104-50-7 EC-No.: 203-208-1 REACH-no: 01-2120793635- 41	2.7 – 5.3	Skin Irrit. 2, H315
Cedramber	CAS-No.: 19870-74-7 EC-No.: 243-384-7	1.1 – 2.2	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1B, H317
Cyclamal	CAS-No.: 103-95-7 EC-No.: 203-161-7 REACH-no: 01-2119970582- 32	0.8 – 1.5	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	0.7 – 1.4	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Jasmal	CAS-No.: 18871-14-2 EC-No.: 242-640-5	0.7 – 1.3	Aquatic Chronic 3, H412
Triplal (Vertocitral)	CAS-No.: 68039-49-6 EC-No.: 268-264-1	0.5 – 0.9575	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
acetophenone substance with national workplace exposure limit(s) (BE, BG, DK, ES, FI, HU, IE, LT, LV, PL, PT, RO)	CAS-No.: 98-86-2 EC-No.: 202-708-7 EC Index-No.: 606-042-00-1 REACH-no: 01-2119533169- 37	0.2 – 0.3	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	0.1 – 0.22	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
decyl alcohol substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.014	Aquatic Chronic 3, H412
Aldehyde C-6 substance with national workplace exposure limit(s) (FI, PL)	CAS-No.: 66-25-1 EC-No.: 200-624-5	0 – 0.0035	Flam. Liq. 3, H226
Caproic acid substance with national workplace exposure limit(s) (BG, LT, LV)	CAS-No.: 142-62-1 EC-No.: 205-550-7	0 – 0.0002	Eye Dam. 1, H318 Skin Corr. 1C, H314
Butyric acid substance with national workplace exposure limit(s) (BG, LT, LV, RO)	CAS-No.: 107-92-6 EC-No.: 203-532-3 EC Index-No.: 607-135-00-X	0 – 0.0001	Skin Corr. 1B, H314

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
-------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency

personnel Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning : Take up liquid spill into absorbent material.
up Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Storage temperature : 25 °C
Storage area : Store in a well-ventilated place. Store away from heat.
Special rules on packaging : Store in a closed container.
Packaging materials : Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m ³
IOEL TWA [ppm]	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m ³ (mixed isomers)
MAK (OEL TWA) [ppm]	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures)
MAK (OEL STEL) [ppm]	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	308 mg/m ³
GVI (OEL TWA) [2]	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA [1]	309 mg/m ³
OEL TWA [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	310 mg/m ³
HTP (OEL TWA) [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m ³ (restrictive limit)
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	310 mg/m ³ (isomer mixture)
AGW (OEL TWA) [2]	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	900 mg/m ³
OEL STEL [ppm]	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
OEL TWA [2]	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL STEL [ppm]	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	skin - potential for cutaneous exposure

Dipropylene glycol monomethyl ether (34590-94-8)	
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
IPRV (OEL TWA) [ppm]	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL) [ppm]	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy- 2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSch (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy- 2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
OEL TWA [ppm]	50 ppm (indicative limit value)
OEL STEL [ppm]	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	308 mg/m ³
NPHV (OEL TWA) [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	308 mg/m ³
OEL STEL [ppm]	50 ppm
OEL chemical category	Potential for cutaneous absorption

Dipropylene glycol monomethyl ether (34590-94-8)**Spain - Occupational Exposure Limits**

VLA-ED (OEL TWA) [1]	308 mg/m ³ (indicative limit value)
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption

Sweden - Occupational Exposure Limits

NGV (OEL TWA)	300 mg/m ³
NGV (OEL TWA) [ppm]	50 ppm
KTV (OEL STEL)	450 mg/m ³
KTV (OEL STEL) [ppm]	75 ppm
OEL chemical category	Skin notation

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	308 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
WEL STEL (OEL STEL) [ppm]	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption

Norway - Occupational Exposure Limits

Grenseverdi (OEL TWA) [1]	300 mg/m ³
Grenseverdi (OEL TWA) [2]	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)
OEL chemical category	Skin notation

Switzerland - Occupational Exposure Limits

MAK (OEL TWA) [1]	300 mg/m ³ (aerosol, vapour)
MAK (OEL TWA) [2]	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
KZGW (OEL STEL) [ppm]	50 ppm (aerosol, vapour)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route

acetophenone (98-86-2)**Belgium - Occupational Exposure Limits**

OEL TWA	50 mg/m ³
OEL TWA [ppm]	10 ppm

Bulgaria - Occupational Exposure Limits

OEL TWA	5 mg/m ³
---------	---------------------

Denmark - Occupational Exposure Limits

OEL TWA [1]	49 mg/m ³
-------------	----------------------

acetophenone (98-86-2)	
OEL TWA [2]	10 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	25 mg/m ³
HTP (OEL TWA) [2]	5 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	50 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	49 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	147 mg/m ³ (calculated)
OEL STEL [ppm]	30 ppm (calculated)
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
OEL chemical category	Skin notation
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	50 mg/m ³
NDSch (OEL STEL)	100 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	10 ppm
Romania - Occupational Exposure Limits	
OEL TWA	100 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	200 mg/m ³
OEL STEL [ppm]	41 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	50 mg/m ³
VLA-ED (OEL TWA) [2]	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	10 ppm
decyl alcohol (112-30-1)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	66 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)

decyl alcohol (112-30-1)	
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	100 mg/m ³
OEL TWA [ppm]	15 ppm
OEL STEL	200 mg/m ³
OEL STEL [ppm]	30 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	66 mg/m ³ (aerosol, vapour)
MAK (OEL TWA) [2]	10 ppm (aerosol, vapour)
KZGW (OEL STEL)	66 mg/m ³ (aerosol, vapour)
KZGW (OEL STEL) [ppm]	10 ppm (aerosol, vapour)
Aldehyde C-6 (66-25-1)	
Finland - Occupational Exposure Limits	
HTP (OEL STEL)	42 mg/m ³
HTP (OEL STEL) [ppm]	10 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	40 mg/m ³
NDSch (OEL STEL)	80 mg/m ³
Caproic acid (142-62-1)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
Butyric acid (107-92-6)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
OEL TWA [ppm]	4 ppm

Butyric acid (107-92-6)	
OEL STEL	30 mg/m ³
OEL STEL [ppm]	8 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls: Ensure good ventilation of the work station.

8.2.2. Personal protection equipment Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable

Freezing point	:Not available
Boiling point	:Not available
Flammability	:Not available
Explosive limits	:Not available
Lower explosion limit	:Not available
Upper explosion limit	:Not available
Flash point	: 83 °C (closed cup) ASTM D7094
Auto-ignition temperature	:Not available :
Decomposition temperature	Not available :
pH	Not available :
Viscosity, kinematic	Not available :
Solubility	Not available :
Partition coefficient n-octanol/water (Log Kow)	Not available :
Vapour pressure	Not available :
Vapour pressure at 50°C	Not available :
Density	Not available :
Relative density	Not available :
Relative vapour density at 20°C	Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard

classes No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg

Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 dermal rabbit	9500 mg/kg
Vertenex (32210-23-4)	
LD50 oral rat	5 g/kg
LD50 oral	3370 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg
Stemone (22457-23-4)	
LD50 oral rat	3800 mg/kg
LD50 oral	3500 mg/kg bodyweight
GAMMA-OCTALACTONE (104-50-7)	
LD50 oral rat	4400 mg/kg
LD50 oral	4400 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg
Cyclamal (103-95-7)	
LD50 oral rat	3810 mg/kg
LD50 oral	3810 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg
COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg
LD50 oral	500 mg/kg bodyweight
LD50 dermal rat	293 mg/kg
Jasmal (18871-14-2)	
LD50 oral rat	> 5 g/kg
LD50 dermal rat	> 2000 mg/kg
Triplal (Vertocitral) (68039-49-6)	
LD50 oral	3900 mg/kg bodyweight
acetophenone (98-86-2)	
LD50 oral rat	900 mg/kg
LD50 oral	500 mg/kg bodyweight
LD50 dermal rat	3300 mg/kg
LC50 Inhalation - Rat	> 2.13 mg/l (Exposure time: 8 h)
Benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg
LD50 oral	1500 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg
LD50 dermal	4000 mg/kg bodyweight
decyl alcohol (112-30-1)	
LD50 oral rat	4720 mg/kg

decyl alcohol (112-30-1)	
LD50 dermal rabbit	3560 mg/kg
Aldehyde C-6 (66-25-1)	
LD50 oral rat	4890 mg/kg
LD50 dermal rabbit	> 8100 mg/kg
Caproic acid (142-62-1)	
LD50 oral rat	3 g/kg
LD50 oral	4000 mg/kg bodyweight
LD50 dermal rabbit	630 mg/kg
Butyric acid (107-92-6)	
LD50 oral rat	2 g/kg
LD50 oral	1630 mg/kg bodyweight
LD50 dermal rabbit	530 mg/kg
Skin corrosion/irritation Serious	: Causes skin irritation.
eye damage/irritation	: Not classified
Respiratory or skin	: May cause an allergic skin reaction.
sensitisation Germ cell	: Not classified
mutagenicity Carcinogenicity	: Not classified
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Vertenex (32210-23-4)	
LC50 - Fish [1]	8.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])

acetophenone (98-86-2)	
LC50 - Fish [1]	162 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	155 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l
decyl alcohol (112-30-1)	
LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Aldehyde C-6 (66-25-1)	
LC50 - Fish [1]	12 – 16.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Caproic acid (142-62-1)	
LC50 - Fish [1]	306 – 334 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Butyric acid (107-92-6)	
EC50 72h - Algae [1]	46.7 mg/l (Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)
Vertenex (32210-23-4)	
Partition coefficient n-octanol/water (Log Pow)	4.8 (at 25 °C)
Stemone (22457-23-4)	
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 30 °C (at pH 7)
GAMMA-OCTALACTONE (104-50-7)	
Partition coefficient n-octanol/water (Log Pow)	1.89 (at 25 °C (at pH 6.4)
Cyclamal (103-95-7)	
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C)
Jasmal (18871-14-2)	
Partition coefficient n-octanol/water (Log Pow)	3.2 – 3.7 (at 25 °C)
acetophenone (98-86-2)	
Partition coefficient n-octanol/water (Log Pow)	1.63 – 1.65

Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
decyl alcohol (112-30-1)	
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 25 °C (at pH 6)
Aldehyde C-6 (66-25-1)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 5)
Caproic acid (142-62-1)	
Partition coefficient n-octanol/water (Log Pow)	1.88
Butyric acid (107-92-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 (at 25 °C (at pH 3)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods HP Code	: Dispose of contents/container in accordance with licensed collector's sorting instructions. : HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment
---------------------------------	---

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				


14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6
Special provisions (ADR) Limited quantities (ADR) Excepted quantities (ADR) Packing instructions (ADR) Special packing provisions (ADR) Mixed packing provisions (ADR) : 274, 335, 375, 601
: 5I
: E1
: P001, IBC03, LP01, R001
: PP1
: MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13

Hazard identification number (Kemler No.) Orange plates : 90



Tunnel restriction code (ADR) : -
 EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E1
 Packing instructions (IMDG) : LP01, P001
 Special packing provisions (IMDG) : PP1
 IBC packing instructions (IMDG) : IBC03
 Tank instructions (IMDG) : T4
 Tank special provisions (IMDG) : TP1, TP29
 EmS-No. (Fire) : F-A
 EmS-No. (Spillage) : S-F
 Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
 PCA Limited quantities (IATA) : Y964
 PCA limited quantity max net quantity (IATA) : 30kgG
 PCA packing instructions (IATA) : 964
 PCA max net quantity (IATA) : 450L
 CAO packing instructions (IATA) : 964
 CAO max net quantity (IATA) : 450L
 Special provisions (IATA) : A97, A158, A197, A215
 ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
 Special provisions (ADN) : 274, 335, 375, 601
 Limited quantities (ADN) : 5 L
 Excepted quantities (ADN) : E1
 Carriage permitted (ADN) : T
 Equipment required (ADN) : PP
 Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
 Special provisions (RID) : 274, 335, 375, 601
 Limited quantities (RID) : 5L
 Excepted quantities (RID) : E1
 Packing instructions (RID) : P001, IBC03, LP01, R001
 Special packing provisions (RID) : PP1
 Mixed packing provisions (RID) : MP19
 Portable tank and bulk container instructions (RID) : T4
 Portable tank and bulk container special provisions (RID) : TP1, TP29
 Tank codes for RID tanks (RID) : LGBV
 Transport category (RID) : 3
 Special provisions for carriage – Packages (RID) : W12
 Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31

Colis express (express parcels) (RID) : CE8
 Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Aldehyde C-6	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	DATE NIGHT; Iso E Super ; Vertenex ; GAMMA-OCTALACTONE ; Cedramber ; Cyclamal ; Triplal (Vertocitral) ; acetophenone ; Benzyl benzoate ; Caproic acid ; Butyric acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	DATE NIGHT; Iso E Super ; Stemone ; Cedramber ; Cyclamal ; Jasmal ; Triplal (Vertocitral) ; Benzyl benzoate ; decyl alcohol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Aldehyde C-6	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Germany

Employment restrictions

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
 Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : Triplal (Vertocitral) is listed

SZW-lijst van mutagene stoffen : Triplal (Vertocitral) is listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Borstvoeding SZW-lijst van reprotoxische stoffen – : None of the components are listed
 Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
 Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Full text of H- and EUH-statements:	
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.