Version: 1

# **OLIVIANDERS FO-0009**

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Product name : OLIVIANDERS FO-0009 HE : NMAU-S4N9-F007-QQD5

Product code : FO-0009

Type of product : Perfumes, fragrances Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only

Use of the substance/mixture : Perfumes, fragrances Function or use category : Odour agents

# 1.2.2. Uses advised against No additional information available

## 1.3. Details of the supplier of the safety data sheet

## **Fragrance Orchard**

Neutrino, Albert Road, Essex CM7 3JQ GB - United Kingdom hello@fragranceorchard.com

### 1.4. Emergency telephone number

: +44 (0) 1376 555185 **Emergency number** 

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315 H319 Serious eye damage/eye irritation, Category 2 Skin sensitisation, Category 1 H317 Hazardous to the aquatic environment - Chronic Hazard, Category 1 H410

Full text of H- and EUH-statements: see section 16

## Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation. Very toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

#### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP) : Warning

Contains : Iso E Super; Vertenex; Amberwood F; Cinnamic alcohol; beta-Caryophyllene

Version: 1

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

 $\ensuremath{\mathsf{P272}}$  - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

orotection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Iso E Super	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989- 04	7.9 – 15.88	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Hexamethylindanopyran	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227- 29	5.9 – 11.84	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	5.9 – 11.7	Not classified
Vertenex	CAS-No.: 32210-23-4 EC-No.: 250-954-9 REACH-no: 01-2119976286- 24	4 – 8	Skin Sens. 1B, H317
Methyl ionone (mixture of isomers)	CAS-No.: 1335-46-2 EC-No.: 215-635-0	3.1 – 6.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411
Amberwood F	CAS-No.: 58567-11-6 EC-No.: 261-332-1	2.6 – 5.16	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Patchouli oil	CAS-No.: 8014-09-3 EC Index-No.: 616-944-7	2.4 – 4.8	Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Version: 1

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ambercore	CAS-No.: 139504-68-0 EC-No.: 412-300-2 EC Index-No.: 603-154-00-2 REACH-no: 01-0000015959-	2 – 3.9	Aquatic Chronic 2, H411
Phenylethyl alcohol	CAS-No.: 60-12-8 EC-No.: 200-456-2 REACH-no: 01-2119963921- 31	1.7 – 3.44	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Bacdanol	CAS-No.: 28219-61-6 EC-No.: 248-908-8 REACH-no: 01-2119529224- 45	1.6 – 3.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 1, H410
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314- 33	1.5 – 3	Aquatic Chronic 2, H411
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	1.3 – 2.56	Eye Irrit. 2, H319
Cinnamic alcohol	CAS-No.: 104-54-1 EC-No.: 203-212-3 REACH-no: 01-2119934496- 29	1.3 – 2.56	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
beta-lonone	CAS-No.: 14901-07-6 EC-No.: 238-969-9	0.8 – 1.52	Aquatic Chronic 2, H411
beta-Caryophyllene	CAS-No.: 87-44-5 EC-No.: 201-746-1 REACH-no: 01-2120745237- 53	0.2 – 0.4	Skin Sens. 1B, H317 Asp. Tox. 1, H304
Isopropyl quinoline	CAS-No.: 135-79-5 EC-No.: 205-220-2	0.1 – 0.16	Acute Tox. 2 (Dermal), H310 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315
Benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	0 – 0.08	Acute Tox. 4 (Oral), H302

Full text of H- and EUH-statements: see section 16

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Version: 1

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin : Irritation. May cause an allergic skin reaction.

contact Symptoms/effects after eye : Eye irritation.

contact

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency

personnel Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

## 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear

personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product. Contaminated work clothing should

not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Version: 1

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

# 7.3. Specific end use(s)

No additional information available

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# 8.1.1 National occupational exposure and biological limit values

Dipropylene glycol monomethyl ether (34590-94-8)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	308 mg/m³	
IOEL TWA [ppm]	50 ppm	
Remark	Possibility of significant uptake through the skin	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	307 mg/m³ (mixed isomers)	
MAK (OEL TWA) [ppm]	50 ppm (mixed isomers)	
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)	
MAK (OEL STEL) [ppm]	100 ppm (isomers mixtures)	
OEL chemical category	Skin notation	
Belgium - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin, Skin notation	
Bulgaria - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	308 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
OEL chemical category	Skin notation	
Cyprus - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin-potential for cutaneous absorption	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	270 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	309 mg/m³	
OEL TWA [2]	50 ppm	

6 Issue Date: 24/04/2023 Version: 1

Dipropylene glycol monomethyl ether (34590-94-8)		
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	310 mg/m³	
HTP (OEL TWA) [2]	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
France - Occupational Exposure Limits		
VME (OEL TWA)	308 mg/m³ (restrictive limit)	
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)	
OEL chemical category	Risk of cutaneous absorption	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	310 mg/m³ (isomer mixture)	
AGW (OEL TWA) [2]	50 ppm (isomer mixture)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	600 mg/m³	
OEL TWA [ppm]	100 ppm	
OEL STEL	900 mg/m³	
OEL STEL [ppm]	150 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	308 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	308 mg/m³ ((2-Methoxymethylethoxy)propanol)	
OEL TWA [2]	50 ppm ((2-Methoxymethylethoxy)propanol)	
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)	
OEL STEL [ppm]	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)	
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	skin - potential for cutaneous absorption	

Version: 1

OEL TWA (ppm) 50 pm OEL Arwincial catagory skin - potential for cutaneous exposure  Lithuania - Occupational Exposure Limits  PRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol) PRV (OEL STEL) pm) 50 pm (2-(2-Methoxypropoxy)-propanol) PRV (OEL STEL) pm] 75 pm (2-(2-Methoxypropoxy)-propanol) PRV (OEL STEL) pm] 75 pm (2-(2-Methoxypropoxy)-propanol) PRV (OEL STEL) pm] 75 pm (2-(2-Methoxypropoxy)-propanol) OEL OEL STEL) pm] 75 pm (2-(2-Methoxypropoxy)-propanol) OEL OEL TWA (ppm) 75 pm (2-(2-Methoxypropoxy)-propanol) OEL TWA (ppm) 75 pm (pmduter of isomers: 1-(2-Methoxypropanolous)-propanolous)-propanolous-propa	Dipropylene glycol monomethyl ether (34590	-94-8)	
OEL TWA [pm] 50 pm  OEL chemical category skin - potential for cutaneous exposure  Lithuania - Occupational Exposure Limits  PRV (OEL TWA) [pm] 50 ppm (2-(2-Methoxypropoxy)-propanol)  IPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol)  IPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol)  IPRV (OEL STEL) [pm] 75 ppm (2-(2-Methoxypropoxy)-propanol)  IPRV (OEL STEL) [pm] 80 mg/m²  OEL TWA [pm] 90 ppm  OEL Chemical category Possibility of significant uptake through the skin  Matta - Occupational Exposure Limits  OEL TWA [pm] 90 ppm  OEL Chemical category Possibility of significant uptake through the skin  Notherlands - Occupational Exposure Limits  TGG-8u (OEL TWA) 300 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylet	Latvia - Occupational Exposure Limits		
Skin - potential for cutaneous exposure  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA) [ppm] 50 ppm (2-(2-Methoxypropoxy)-propanol)  TPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol)  TPRV (OEL STEL) [ppm] 75 ppm (2-(2-Methoxypropoxy)-propanol)  TPRV (OEL STEL) [ppm] 75 ppm (2-(2-Methoxypropoxy)-propanol)  OEL chemical category Skin notation  Luxembourg - Occupational Exposure Limits  OEL TWA [ppm] 50 ppm  OEL Chemical category Possibility of significant uptake through the skin  Malta - Occupational Exposure Limits  OEL TWA [ppm] 50 ppm  OEL Chemical category Possibility of significant uptake through the skin  Malta - Occupational Exposure Limits  OEL TWA [ppm] 50 ppm  OEL Chemical category Possibility of significant uptake through the skin  More of the skin Possibility of significant uptake through the skin  OEL TWA [ppm] 50 ppm  OEL Chemical category Possibility of significant uptake through the skin  Notherlands - Occupational Exposure Limits  TGG-8u (DEL TWA) 300 mg/m²  Poland - Occupational Exposure Limits  NOS (DEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methox	OEL TWA	308 mg/m³	
Lithuania - Occupational Exposure Limits  IPRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol)  IPRV (OEL TWA) [ppm] 50 ppm (2-(2-Methoxypropoxy)-propanol)  TPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol)  TPRV (OEL STEL) [ppm] 75 ppm (2-(2-Methoxypropoxy)-propanol)  TPRV (OEL STEL) [ppm] 75 ppm (2-(2-Methoxypropoxy)-propanol)  OEL Othermical category Skin notation  Luxembourg - Occupational Exposure Limits  OEL TWA 308 mg/m²  OEL TWA 50 ppm 50 ppm  OEL Chemical category Possibility of significant uptake through the skin  Malta - Occupational Exposure Limits  OEL TWA 308 mg/m²  OEL TWA 308 mg/m²  OEL TWA 90 ppm 50 ppm  OEL Chemical category Possibility of significant uptake through the skin  Morterlands - Occupational Exposure Limits  TGG-8u (OEL TWA) 300 mg/m²  Polands - Occupational Exposure Limits  NDS (OEL TWA) 300 mg/m²  Polands - Occupational Exposure Limits  NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-	OEL TWA [ppm]	50 ppm	
IPRV (OEL TWA)   300 mg/m² (2-(2-Methoxypropoxy)-propanol)   IPRV (OEL TWA) [ppm]   50 ppm (2-(2-Methoxypropoxy)-propanol)   IPRV (OEL STEL)   450 mg/m² (2-(2-Methoxypropoxy)-propanol)   IPRV (OEL STEL)   50 ppm   75 ppm (2-(2-Methoxypropoxy)-propanol)   IPRV (OEL STEL)   50 ppm   75 ppm (2-(2-Methoxypropoxy)-propanol)   IPRV (OEL STEL)   50 ppm   75 ppm   75 ppm   Intermedial category   50 ppm   50 ppm   Intermedial category   50 ppm   50 ppm   50 ppm   Intermedial category   50 ppm   50 ppm   50 ppm   Intermedial category   50 ppm   50 ppm   50 ppm   50 ppm   INTERMEDIAL   50 ppm   50 ppm	OEL chemical category	skin - potential for cutaneous exposure	
PRV (OEL TWA)   [ppm]   50 ppm (2-(2-Methoxypropoxy)-propanol)	Lithuania - Occupational Exposure Limits		
TPRV (OEL STEL)   450 mg/m³ (2-(2-Methoxypropoxy)-propanol)  TPRV (OEL STEL) [ppm] 75 ppm (2-(2-Methoxypropoxy)-propanol)  OEL chemical category Skin notation  Luxembourg - Occupational Exposure Limits  OEL TWA 308 mg/m³  OEL TWA [ppm] 50 ppm  OEL chemical category Possibility of significant uptake through the skin  Maita - Occupational Exposure Limits  OEL TWA 308 mg/m³  OEL TWA [ppm] 50 ppm  OEL chemical category Possibility of significant uptake through the skin  Maita - Occupational Exposure Limits  OEL TWA [ppm] 50 ppm  OEL chemical category Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits  TGG-8u (OEL TWA) 300 mg/m³  Poland - Occupational Exposure Limits  NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1	IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
TPRV (OEL STEL) [ppm] 75 ppm (2-(2-Methoxypropoxy)-propanol) OEL chemical category Skin notation  Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m² OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Malta - Occupational Exposure Limits OEL TWA 308 mg/m² OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Malta - Occupational Exposure Limits OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits TGG-9u (OEL TWA) 300 mg/m² Poland - Occupational Exposure Limits NDS (OEL TWA) 300 mg/m² Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m² (indicative limit value) OEL TWA [ppm] 50 ppm (indicative limit value) OEL STEL [ppm] 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value OEL TWA 308 mg/m² OEL TWA [ppm] 50 ppm OEL chemical category Skin notation Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 308 mg/m² NPHV (OEL TWA) [2] 50 ppm OEL chemical category Potential for cutaneous absorption Slovakia - Occupational Exposure Limits OEL Third (I) 308 mg/m² OEL chemical category Potential for cutaneous absorption	IPRV (OEL TWA) [ppm]	50 ppm (2-(2-Methoxypropoxy)-propanol)	
DEL chemical category  Luxembourg - Occupational Exposure Limits  OEL TWA   308 mg/m²   50 ppm  OEL chemical category   Possibility of significant uptake through the skin  Maita - Occupational Exposure Limits  OEL TWA   500 ppm  OEL Chemical category   Possibility of significant uptake through the skin  Maita - Occupational Exposure Limits  OEL TWA   500 ppm  OEL chemical category   Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits  TGG-8u (OEL TWA)   300 mg/m²  Poland - Occupational Exposure Limits  NDS (OEL TWA)   300 mg/m²  Poland - Occupational Exposure Limits  NDS (OEL TWA)   240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)   480 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA   308 mg/m² (indicative limit value)  OEL TWA   500 ppm   50 ppm (indicative limit value)  OEL STEL   5pm   150 ppm   50 pp	TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m² OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 308 mg/m² OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin Notherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m² Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m² (indicative limit value) OEL TWA [ppm] 50 ppm (indicative limit value) OEL STEL [ppm] 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value OEL TWA 308 mg/m² OEL TWA 308 mg/m² OEL TWA [ppm] 50 ppm OEL chemical category skin notation Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 308 mg/m² NPHV (OEL TWA) [2] 50 ppm OEL chemical category Potential for cutaneous absorption	TPRV (OEL STEL) [ppm]	75 ppm (2-(2-Methoxypropoxy)-propanol)	
OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Malta - Occupational Exposure Limits OEL TWA 308 mg/m² OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Melta - Occupational Exposure Limits OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ Poland - Occupational Exposure Limits  NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL) 480 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA 308 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol)  OEL TWA 308 mg/m² (mixture of isomers: 1-(2-M	OEL chemical category	Skin notation	
DEL TWA [ppm] 50 pm  DEL chemical category Possibility of significant uptake through the skin  Malta - Occupational Exposure Limits  DEL TWA 308 mg/m²  DEL themical category Possibility of significant uptake through the skin  DEL TWA [ppm] 50 ppm  DEL chemical category Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits  TGG-8u (DEL TWA) 300 mg/m²  Poland - Occupational Exposure Limits  NDS (DEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (DEL STEL) 480 mg/m² (indicative limit value)  Portugal - Occupational Exposure Limits  DEL TWA 308 mg/m² (indicative limit value)  DEL TWA [ppm] 50 ppm (indicative limit value)  DEL STEL [ppm] 150 ppm  DEL chemical category skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  DEL TWA 308 mg/m²  DEL TWA [ppm] 50 ppm  DEL chemical category Skin notation  Slovakia - Occupational Exposure Limits  NPHV (DEL TWA) [1] 308 mg/m²  NPHV (DEL TWA) [2] 50 ppm  DEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	Luxembourg - Occupational Exposure Limits		
Delic chemical category  Possibility of significant uptake through the skin  Maita - Occupational Exposure Limits  Delic TWA  308 mg/m²  OEL tWA [ppm]  50 ppm  OEL chemical category  Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits  TGG-8u (DEL TWA)  300 mg/m³  Poland - Occupational Exposure Limits  NDS (OEL TWA)  240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)  480 mg/m² (indicative limit value)  Portugal - Occupational Exposure Limits  DEL TWA  308 mg/m² (indicative limit value)  OEL TWA [ppm]  50 ppm (indicative limit value)  OEL STEL [ppm]  0EL STEL [ppm]  150 ppm  OEL chemical category  skin potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  NPHV (DEL TWA) [1]  308 mg/m²  NPHV (OEL TWA) [2]  50 ppm  OEL chemical category  Potential for cutaneous absorption  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [2]  50 ppm  OEL chemical category  Potential for cutaneous absorption	OEL TWA	308 mg/m³	
Malta - Occupational Exposure Limits  OEL TWA   308 mg/m³   50 ppm    OEL chemical category   Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits  TGG-8u (OEL TWA)   300 mg/m²    Poland - Occupational Exposure Limits  NDS (OEL TWA)   240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)   480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA   308 mg/m³ (indicative limit value)  OEL TWA   50 ppm (indicative limit value)  OEL STEL [ppm]   150 ppm  OEL chemical category   skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA   308 mg/m³  OEL Chemical category   Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1]   308 mg/m³  NPHV (OEL TWA) [2]   50 ppm  OEL chemical category   Potential for cutaneous absorption	OEL TWA [ppm]	50 ppm	
OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³  Poland - Occupational Exposure Limits  NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, ad 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA 308 mg/m³ (indicative limit value)  OEL TWA [ppm] 50 ppm (indicative limit value)  OEL STEL [ppm] 150 ppm  OEL chemical category skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA [ppm] 50 ppm  OEL chemical category Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1] 308 mg/m³  NPHV (OEL TWA) [2] 50 ppm  OEL chemical category Potential for cutaneous absorption  Slovania - Occupational Exposure Limits  NPHV (OEL TWA) [2] 50 ppm  OEL chemical category Potential for cutaneous absorption	OEL chemical category	Possibility of significant uptake through the skin	
OEL TWA [ppm] 50 ppm OEL chemical category Possibility of significant uptake through the skin  Netherlands - Occupational Exposure Limits  TGG-8u (OEL TWA) 300 mg/m³  Poland - Occupational Exposure Limits  NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, and 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL) 480 mg/m³ (indicative limit value)  Portugal - Occupational Exposure Limits  OEL TWA 308 mg/m³ (indicative limit value)  OEL TWA [ppm] 50 ppm (indicative limit value)  OEL TWA [ppm] 150 ppm  OEL Chemical category skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA [ppm] 50 ppm  OEL Chemical category 50 ppm  OEL chemical category Potential for cutaneous absorption  Stovakia - Occupational Exposure Limits  NPHV (OEL TWA) [2] 50 ppm  OEL chemical category Potential for cutaneous absorption	Malta - Occupational Exposure Limits		
OEL TWA [ppm] 150 ppm (indicative limit value)  OEL TWA 308 mg/m³ (indicative limit value)  OEL TWA [ppm] 50 ppm (indicative limit value)  OEL TWA [ppm] 50 ppm  OEL chemical category skin - potential for cutaneous exposure indicative limit value  OEL TWA [ppm] 50 ppm  OEL Chemical category skin notation  Siovakia - Occupational Exposure Limits  OEL TWA [ppm] 50 ppm  OEL Chemical category Skin notation	OEL TWA	308 mg/m³	
Note rlands - Occupational Exposure Limits  TGG-8u (OEL TWA)  Poland - Occupational Exposure Limits  NDS (OEL TWA)  240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)  480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA  308 mg/m³ (indicative limit value)  OEL TWA [ppm]  50 ppm (indicative limit value)  OEL STEL [ppm]  150 ppm  OEL chemical category  skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA [ppm]  50 ppm  Solo ppm  Skin notation  Siovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1]  308 mg/m³  NPHV (OEL TWA) [2]  50 ppm  OEL chemical category  Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	OEL TWA [ppm]	50 ppm	
TGG-8u (OEL TWA)  Poland - Occupational Exposure Limits  NDS (OEL TWA)  240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)  480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA  308 mg/m³ (indicative limit value)  OEL TWA [ppm]  50 ppm (indicative limit value)  OEL STEL [ppm]  150 ppm  OEL chemical category  skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA [ppm]  50 ppm  OEL twA [ppm]  50 ppm  Skin notation  Siovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1]  308 mg/m³  NPHV (OEL TWA) [2]  50 ppm  OEL chemical category  Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	OEL chemical category	Possibility of significant uptake through the skin	
Poland - Occupational Exposure Limits  NDS (OEL TWA)  240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)  480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA  308 mg/m³ (indicative limit value)  OEL TWA [ppm]  50 ppm (indicative limit value)  OEL STEL [ppm]  50 ppm (skin - potential for cutaneous exposure indicative limit value)  Romania - Occupational Exposure Limits  OEL TWA  308 mg/m³  OEL TWA [ppm]  50 ppm  OEL chemical category  Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1]  308 mg/m³  NPHV (OEL TWA) [2]  50 ppm  OEL chemical category  Potential for cutaneous absorption  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [2]  50 ppm  Potential for cutaneous absorption	Netherlands - Occupational Exposure Limits		
NDS (OEL TWA)  240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)  480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA  308 mg/m³ (indicative limit value)  OEL TWA [ppm]  50 ppm (indicative limit value)  OEL STEL [ppm]  50 ppm (indicative limit value)  OEL chemical category  skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA  308 mg/m³  OEL TWA [ppm]  50 ppm  OEL chemical category  Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1]  308 mg/m³  NPHV (OEL TWA) [2]  50 ppm  OEL chemical category  Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits  NPHV (OEL TWA) [2]  50 ppm  OEL chemical category  Potential for cutaneous absorption	TGG-8u (OEL TWA)	300 mg/m³	
2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  NDSCh (OEL STEL)  480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA  308 mg/m³ (indicative limit value)  OEL TWA [ppm]  50 ppm (indicative limit value)  OEL STEL [ppm]  150 ppm  OEL chemical category  skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  50 ppm  OEL chemical category  Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1]  308 mg/m³  NPHV (OEL TWA) [2]  OEL chemical category  Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits  Potential for cutaneous absorption	Poland - Occupational Exposure Limits		
2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)  Portugal - Occupational Exposure Limits  OEL TWA	NDS (OEL TWA)		
OEL TWA [ppm] 50 ppm (indicative limit value) OEL TWA [ppm] 150 ppm (indicative limit value) OEL STEL [ppm] 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ OEL TWA 308 mg/m³ OEL TWA [ppm] 50 ppm OEL chemical category Skin notation  Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 308 mg/m³ NPHV (OEL TWA) [2] 50 ppm OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	NDSCh (OEL STEL)		
OEL TWA [ppm] 50 ppm (indicative limit value)  OEL STEL [ppm] 150 ppm  OEL chemical category skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits  OEL TWA 308 mg/m³  OEL TWA [ppm] 50 ppm  OEL chemical category Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1] 308 mg/m³  NPHV (OEL TWA) [2] 50 ppm  OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	Portugal - Occupational Exposure Limits		
OEL STEL [ppm] 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value  Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ OEL TWA [ppm] 50 ppm OEL chemical category Skin notation  Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 308 mg/m³ NPHV (OEL TWA) [2] 50 ppm OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	OEL TWA	308 mg/m³ (indicative limit value)	
Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ OEL TWA [ppm] 50 ppm OEL chemical category Skin notation  Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [1] 308 mg/m³ OEL chemical category Potential for cutaneous absorption  Slovakia - Occupational Exposure Limits NPHV (OEL TWA) [2] 50 ppm OEL chemical category Potential for cutaneous absorption	OEL TWA [ppm]	50 ppm (indicative limit value)	
Romania - Occupational Exposure Limits  OEL TWA	OEL STEL [ppm]	150 ppm	
OEL TWA [ppm] 50 ppm OEL chemical category Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1] 308 mg/m³  NPHV (OEL TWA) [2] 50 ppm OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	OEL chemical category	skin - potential for cutaneous exposure indicative limit value	
OEL TWA [ppm] 50 ppm OEL chemical category Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1] 308 mg/m³  NPHV (OEL TWA) [2] 50 ppm OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	Romania - Occupational Exposure Limits		
OEL chemical category  Skin notation  Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1]  NPHV (OEL TWA) [2]  OEL chemical category  Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	OEL TWA	308 mg/m³	
Slovakia - Occupational Exposure Limits  NPHV (OEL TWA) [1] 308 mg/m³  NPHV (OEL TWA) [2] 50 ppm  OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	OEL TWA [ppm]	50 ppm	
NPHV (OEL TWA) [1] 308 mg/m³  NPHV (OEL TWA) [2] 50 ppm  OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	OEL chemical category	Skin notation	
NPHV (OEL TWA) [2] 50 ppm  OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	Slovakia - Occupational Exposure Limits	•	
OEL chemical category Potential for cutaneous absorption  Slovenia - Occupational Exposure Limits	NPHV (OEL TWA) [1]	308 mg/m³	
Slovenia - Occupational Exposure Limits	NPHV (OEL TWA) [2]	50 ppm	
	OEL chemical category	Potential for cutaneous absorption	
OFL TWA 308 mg/m³	Slovenia - Occupational Exposure Limits		
·····	OEL TWA	308 mg/m³	

Version: 1

OEL STEL         308 mgm²           OEL STEL (ppm)         50 ppm           OEL STEL (ppm)         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA) [7]         308 mg/m² (indicative limit value)           NLA-ED (OEL TWA) [7]         50 ppm (indicative limit value)           CEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NOS (OEL TWA) [7]         50 ppm (indicative limit value)           NOS (OEL TWA) [7]         50 ppm (indicative limit value)           NOS (OEL TWA) [7]         50 ppm (indicative limit value)           NOS (OEL TWA) [7]         50 ppm (indicative limit value)           NOS (OEL TWA) [7]         450 mg/m²           NOS (OEL TWA) [7]         450 mg/m²           NOS (OEL TWA) [7]         50 ppm           NOS (OEL TWA) [7]         90 ppm (calculated)           NOS mg/m² (acroso) (appun)           NOS mg/m² (acroso) (appun) <th>Dipropylene glycol monomethyl ether (34590-</th> <th>94-8)</th>	Dipropylene glycol monomethyl ether (34590-	94-8)	
OEL STEL [ppm]         50 ppm           OEL chemical category         Potential for cutaneous absorption           Spain-Occupational Exposure Limits           VLA-ED (OEL TWA) [1]         308 mg/m² (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NGY (OEL TWA) [ppm]         50 ppm           NGY (OEL TWA) [ppm]         50 ppm           KTY (OEL STEL) [ppm]         450 mg/m²           KTY (OEL STEL) [ppm]         75 ppm           OEL chemical category         8 kin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m²           WEL STEL (OEL STEL) [ppm]         150 ppm           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         300 mg/m² (calculated)           WEL STEL (OEL STEL) [ppm]         50 ppm           Norway - Occupational Exposure Limits           WEL STEL (OEL STEL) [ppm]         300 mg/m² (calculated)           WEL STEL (OEL STEL) [ppm]         300 mg/m² (calculated)           Norway - Occupat	OEL TWA [ppm]	50 ppm	
OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA) [1]         308 mg/m² (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NGY (OEL TWA) [pm]         300 mg/m²           NGY (OEL TWA) [pm]         50 ppm           KTV (OEL STEL) [pm]         450 mg/m²           KTV (OEL STEL) [pm]         75 ppm           OEL chemical category         50m modation           VERL TWA (OEL TWA) [1]         308 mg/m²           WEL TWA (OEL TWA) [2]         50 ppm           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           Well chemical category         150 ppm (calculated)           Well chemical (CEL TWA) [1]         300 mg/m² (calculated) <tr< td=""><td>OEL STEL</td><td>308 mg/m³</td></tr<>	OEL STEL	308 mg/m³	
Spain - Occupational Exposure Limits           VLA-ED (OEL TWA) [1]         308 mg/m* (indicative limit value)           VLA-ED (OEL TWA) [2]         50 ppm (indicative limit value)           OEL chemical category         six potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NGV (OEL TWA)         300 mg/m²           NGV (OEL TWA)         50 ppm           KTV (OEL STEL)         450 mg/m²           KTV (OEL STEL) [ppm]         75 ppm           OEL chemical category         75 ppm           OEL chemical category         308 mg/m²           WEL TWA (OEL TWA) [1]         308 mg/m²           WEL TWA (OEL TWA) [2]         50 ppm           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL TWA) [1]         300 mg/m²           Grosseverdi (OEL TWA) [2]         50 ppm           Grosseverdi (OEL TWA) [2]         50 ppm           Kortidsverdi (OEL TWA) [2]         50 ppm           Kortidsverdi (OEL TWA) [2]         50 ppm (value calculated)           Kortidsverdi (OEL TWA) [2]         50 ppm (value calculated)           Kortidsverdi (OEL STEL) [ppm]	OEL STEL [ppm]	50 ppm	
VLA-ED (OEL TWA) [1]         308 mg/m² (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NGV (OEL TWA) [2]         300 mg/m²           NGV (OEL TWA) [2]         50 ppm           KTV (OEL STEL)         450 mg/m²           KTV (OEL STEL) [2] [2] [2] [2] [2] [2] [2] [2] [2] [2]	OEL chemical category	Potential for cutaneous absorption	
VLA-ED (OEL TWA) [2]         50 ppm (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NGV (OEL TWA)         300 mg/m³           NGV (OEL TWA) [pm]         50 ppm           KTV (OEL STEL) [pm]         50 ppm           KTV (OEL STEL) [pm]         75 pm           OEL chemical category         8kin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m²           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (DEL STEL)         924 mg/m² (calculated)           WEL STEL (OEL STEL) [pm]         150 ppm (calculated)           WEL STEL (OEL STEL) [pm]         160 ppm (calculated)           WEL STEL (OEL STEL) [pm]         300 mg/m²           Genseverdi (OEL TWA) [1]         300 mg/m²           Grosseverdi (OEL TWA) [2]         50 ppm           Kortidsverdi (OEL STEL) [pm]         75 ppm (value calculated)           Kortidsverdi (OEL STEL) [pm]         75 ppm (value calculated)           Swizerland - Occupational Exposure Limits           MK (OEL TWA) [2]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [pm]         300 mg/m² (aerosol, vapour) <td>Spain - Occupational Exposure Limits</td> <td></td>	Spain - Occupational Exposure Limits		
OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NGY (OEL TWA)         300 mg/m²           NGY (OEL TWA) [pm]         50 ppm           KTV (OEL STEL)         450 mg/m²           KTV (OEL STEL) [ppm]         75 ppm           OEL chemical category         8kin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m²           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (DEL STEL)         924 mg/m² (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         9 potential for cutaneous absorption           Norway - Occupational Exposure Limits           Seppem           Genseverdi (OEL TWA) [1]         300 mg/m² (calculated)           Kortidsverdi (OEL STEL) [ppm]         35 ppm           Kortidsverdi (OEL STEL) [ppm]         375 mg/m² (value calculated)           Kortidsverdi (OEL STEL) [ppm]         30 mg/m² (aerosol, vapour)           Kortidsverdi (OEL STEL) [ppm]         30 mg/m² (aerosol, vapour)           Kaccurational Exposure Limits         30 mg/m² (aerosol, v	VLA-ED (OEL TWA) [1]	308 mg/m³ (indicative limit value)	
Swedon - Occupational Exposure Limits           NSV (OEL TWA)         300 mg/m²           NGV (OEL TWA) (ppm]         50 ppm           KTV (OEL STEL)         450 mg/m²           KTV (OEL STEL) (ppm]         75 ppm           OEL chemical category         8 kin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m³           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           WE conserverid (OEL TWA) [1]         300 mg/m³           Geneseverid (OEL TWA) [2]         375 mg/m³ (value calculated)           Kortidsverid (OEL STEL) [ppm]         75 ppm (value calculated)           Kortidsverid (OEL STEL) [ppm]         90 mg/m³ (aerosol, vapour)           KZGW (OE	VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)	
NGV (OEL TWA) [ppm]         50 ppm           KTV (OEL STEL)         450 mg/m³           KTV (OEL STEL) [ppm]         75 ppm           OEL chemical category         8kin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m³           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         92 mg/m² (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         300 mg/m³           Well STEL (OEL STEL) [ppm]         50 ppm           Kortids (OEL TWA) [1]         300 mg/m³           Grenseverdi (OEL TWA) [2]         50 ppm           Kortidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Kortidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Kortidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Switzerland - Occupational Exposure Limits         Value calculated)           KX (OEL TWA) [2]         50 ppm (aerosol, vapour)           KX (OEL TWA) [2]         50 ppm (aerosol, vapour)           KX (OEL TWA) [2]         50 ppm (aerosol, vapour)           KX (OEL STEL) [ppm]         50 ppm (aerosol, vapour)	OEL chemical category	skin - potential for cutaneous absorption	
NGV (OEL TWA) [ppm]         50 ppm           KTV (OEL STEL)         450 mg/m²           KTV (OEL STEL) [ppm]         75 ppm           OEL chemical category         Skin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m²           WEL STEL (OEL STEL)         924 mg/m² (calculated)           WEL STEL (OEL STEL) [ppm]         924 mg/m² (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         750 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         750 ppm (calculated)           Well STEL (OEL TWA) [1]         300 mg/m² (calculated)           Grenseverdi (OEL TWA) [1]         300 mg/m² (value calculated)           Grenseverdi (OEL TWA) [2]         50 ppm           Kortidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Kottidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Well STEL [ppm]         300 mg/m² (variue calculated)           Well STEL [ppm]         300 mg/m² (aerosol, vapour)           MK (OEL TWA) [1]         300 mg/m² (aerosol, vapour)           K29W (OEL TWA) [2]         50 ppm (aerosol, vapour)           K29W (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           K29W (OEL STEL)	Sweden - Occupational Exposure Limits		
KTY (OEL STEL)         450 mg/m³           KTV (OEL STEL) [ppm]         75 ppm           OEL chemical category         Skin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m³           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         300 mg/m³           Norway - Occupational Exposure Limits           Well stemal category           Nor mg/m³ (value calculated)           Support (Value calculated)           Support (Value calculated)           Nor mg/m³ (value calculated)           Support (Value calculated)           Support (Value calculated)           Nor mg/m³ (value calculated)           Support (Value calculated)           Support (Value calculated)           Support (Value calculated)           Support (Value calculated)           Nor mg/m³ (value calculated) <td>NGV (OEL TWA)</td> <td>300 mg/m³</td>	NGV (OEL TWA)	300 mg/m³	
KTV (OEL STEL) [ppm]         75 ppm           OEL chemical category         skin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m²           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         924 mg/m² (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA) [1]         300 mg/m²           Grenseverdi (OEL TWA) [2]         50 ppm           Kortidosverdi (OEL STEL) [ppm]         375 mg/m² (value calculated)           Kortidosverdi (OEL STEL) [ppm]         5 ppm (value calculated)           Switzerland - Occupational Exposure Limits           MAK (OEL TWA) [1]         300 mg/m² (aerosol, vapour)           KZGW (OEL STEL)         300 mg/m² (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           CSGH OCCUpational Exposure Limits           WGH OCL TWA [ppm]         100 ppm	NGV (OEL TWA) [ppm]	50 ppm	
OEL chemical category         Skin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m³           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA) [1]         300 mg/m³           Grenseverdi (OEL TWA) [2]         50 ppm           Kortidisverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Kortidisverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Gel chemical category         kin notation           Switzerland - Occupational Exposure Limits           MAK (OEL TWA) [1]         300 mg/m³ (aerosol, vapour)           MAK (OEL TWA) [2]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           SWA - ACGIH - Occupational Exposure Limits           WGIH OCCUPATIONAL Exposure Limits           Bop Mg      <	KTV (OEL STEL)	450 mg/m³	
United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         308 mg/m³           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA) [1]         300 mg/m³           Grenseverdi (OEL TWA) [2]         50 ppm           Korttidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Korttidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Kottidsverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Switzerland - Occupational Exposure Limits         Switzerland - Occupational Exposure Limits           MAK (OEL TWA) [1]         300 mg/m³ (aerosol, vapour)           KZGW (OEL STEL)         300 mg/m³ (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         100 ppm           ACGIH - Occupational Exposure Limits         Soppm (aerosol, vapour)           KZGH (DEL TWA) [2]         50 ppm (aerosol, vapour)           KZGW (DEL STEL) [ppm]         <	KTV (OEL STEL) [ppm]	75 ppm	
WEL TWA (OEL TWA) [1]         308 mg/m³           WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           Norway - Occupational Exposure Limits         50 ppm           Kortidosverdi (OEL TWA) [1]         300 mg/m³           Grenseverdi (OEL STEL)         375 mg/m³ (value calculated)           Kortidosverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Kortidosverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Suitzerland - Occupational Exposure Limits         Suitzerland - Occupational Exposure Limits           MAK (OEL TWA) [1]         300 mg/m³ (aerosol, vapour)           MAK (OEL TWA) [2]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         100 ppm           ACGIH - Occupational Exposure Limits         So ppm (aerosol, vapour)           ACGIH CEL TWA [ppm]         150 ppm           ACGIH chemical category         8 kin - potential significant contribution to overall exposure by the cutaneous route           Borzaldehyde (100-52-7)     <	OEL chemical category	Skin notation	
WEL TWA (OEL TWA) [2]         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL STEL (OEL STEL) [ppm]         150 ppm (calculated)           WEL Chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA) [1]         300 mg/m³           Grenseverdi (OEL TWA) [2]         50 ppm           Kortidisverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Kortidisverdi (OEL STEL) [ppm]         75 ppm (value calculated)           Suitzerland - Occupational Exposure Limits         Skin notation           MAK (OEL TWA) [1]         300 mg/m³ (aerosol, vapour)           MAK (OEL TWA) [2]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           KZGW (OEL STEL) [ppm]         50 ppm (aerosol, vapour)           WAS - ACGIH - Occupational Exposure Limits         VAPA - ACGIH - Occupational Exposure Limits           WGIH OEL TWA [ppm]         100 ppm           ACGIH OEL STEL [ppm]         50 ppm           ACGIH OEL STEL [ppm]         50 ppm           ACGIH Oele STEL [ppm]	United Kingdom - Occupational Exposure Limits		
WEL STEL (OEL STEL) 924 mg/m³ (calculated) WEL STEL (OEL STEL) [ppm] 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 300 mg/m³ Grenseverdi (OEL TWA) [2] 50 ppm Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  WEA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL TWA [ppm] 150 ppm  ACGIH OEL STEL [ppm] 150 ppm	WEL TWA (OEL TWA) [1]	308 mg/m³	
WEL STEL (OEL STEL) [ppm] 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 300 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated)  Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  WAS - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL TWA [ppm] 150 ppm  ACGIH OEL STEL [ppm] 50 ppm  ACGIH oenical category 50 kin - potential significant contribution to overall exposure by the cutaneous route  Benzaldeh y Cocupational Exposure Limits	WEL TWA (OEL TWA) [2]	50 ppm	
WEL chemical category  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 300 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Kortidsverdi (OEL STEL) 375 mg/m³ (value calculated)  Kortidsverdi (OEL STEL) [ppm] 75 ppm (value calculated)  OEL chemical category 8kin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 500 ppm (aerosol, vapour)  WAS - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 500 ppm  ACGIH chemical category 8kin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 300 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated)  Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated)  OEL chemical category 8kin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 500 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 500 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 500 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 100 ppm  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 500 ppm  ACGIH chemical category 500 ppm (aerosol, vapour) bpm  ACGIH chemical category 500 ppm  Bulgaria - Occupational Exposure Limits	WEL STEL (OEL STEL) [ppm]	150 ppm (calculated)	
Grenseverdi (OEL TWA) [1] 300 mg/m³ Grenseverdi (OEL TWA) [2] 50 ppm Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) OEL chemical category Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  WSA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	WEL chemical category	Potential for cutaneous absorption	
Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated)  Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated)  OEL chemical category 8kin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 500 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 500 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category 8kin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	Norway - Occupational Exposure Limits		
Korttidsverdi (OEL STEL) [ppm] 75 pm (value calculated)  OEL chemical category Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [ppm] 100 ppm  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	Grenseverdi (OEL TWA) [1]	300 mg/m³	
Korttidsverdi (OEL STEL) [ppm] 75 ppm (value calculated) OEL chemical category Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) 300 mg/m³ (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	Grenseverdi (OEL TWA) [2]	50 ppm	
OEL chemical category  Skitzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) 300 mg/m³ (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category 5kin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)	
Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) 300 mg/m³ (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	
MAK (OEL TWA) [1] 300 mg/m³ (aerosol, vapour)  MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) 300 mg/m³ (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	OEL chemical category	Skin notation	
MAK (OEL TWA) [2] 50 ppm (aerosol, vapour)  KZGW (OEL STEL) [300 mg/m³ (aerosol, vapour)  KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	Switzerland - Occupational Exposure Limits		
KZGW (OEL STEL)  KZGW (OEL STEL) [ppm]  50 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm]  100 ppm  ACGIH OEL STEL [ppm]  150 ppm  ACGIH chemical category  Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	MAK (OEL TWA) [1]	300 mg/m³ (aerosol, vapour)	
KZGW (OEL STEL) [ppm] 50 ppm (aerosol, vapour)  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	MAK (OEL TWA) [2]	50 ppm (aerosol, vapour)	
USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)	
ACGIH OEL TWA [ppm] 100 ppm  ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	KZGW (OEL STEL) [ppm]	50 ppm (aerosol, vapour)	
ACGIH OEL STEL [ppm] 150 ppm  ACGIH chemical category Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	USA - ACGIH - Occupational Exposure Limits		
ACGIH chemical category  Skin - potential significant contribution to overall exposure by the cutaneous route  Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	ACGIH OEL TWA [ppm]	100 ppm	
Benzaldehyde (100-52-7)  Bulgaria - Occupational Exposure Limits	ACGIH OEL STEL [ppm]	150 ppm	
Bulgaria - Occupational Exposure Limits	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route	
	Benzaldehyde (100-52-7)		
OEL TWA 5 mg/m³	Bulgaria - Occupational Exposure Limits		
	OEL TWA	5 mg/m³	

Version: 1

Benzaldehyde (100-52-7)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	4.4 mg/m³
HTP (OEL TWA) [2]	1 ppm
HTP (OEL C)	17.4 mg/m³
HTP (OEL C) [ppm]]	4 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m³
CK (OEL STEL)	10 mg/m³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	10 mg/m³
NDSCh (OEL STEL)	40 mg/m³

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

# 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

# 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:** Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

# Personal protective equipment symbol(s):







# 8.2.2.1. Eye and face protection

## Eye protection:

Safety glasses

### 8.2.2.2. Skin protection

## Skin and body protection:

Wear suitable protective clothing

# Hand protection:

Protective gloves

Version: 1

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

### **Environmental exposure controls:**

Avoid release to the environment.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. : characteristic. Odour : Not available Odour threshold Melting point : Not applicable : Not available Freezing point Boiling point : Not available Flammability : Not available **Explosive limits** : Not available Lower explosion limit : Not available Upper explosion limit : Not available

Flash point : > 93 °C (closed cup) ASTM D7094

Auto-ignition temperature : Not available Decomposition temperature : Not available : Not available Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Not available Vapour pressure Vapour pressure at 50°C Not available Not available Density : Not available Relative density Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

# 9.2. Other information

## 9.2.1. Information with regard to physical hazard classes

No additional information available

## 9.2.2. Other safety characteristics

No additional information available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Version: 1

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

# 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation)	: Not classified	
Hexamethylindanopyran (1222-05-5)		
LD50 oral rat	> 3250 mg/kg	
LD50 dermal rabbit	> 3250 mg/kg	
Dipropylene glycol monomethyl ether (34	4590-94-8)	
LD50 oral rat	5.35 g/kg	
LD50 dermal rabbit	9500 mg/kg	
Vertenex (32210-23-4)	·	
LD50 oral rat	5 g/kg	
LD50 oral	3370 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg	
Methyl ionone (mixture of isomers) (1335-46-2)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg	
LD50 dermal	2900 mg/kg bodyweight	
Amberwood F (58567-11-6)		
LD50 oral rat	> 5 g/kg	
LD50 dermal rabbit	> 5000 mg/kg	
Patchouli oil (8014-09-3)	<del>- :</del>	
LD50 oral rat	> 5 g/kg	
Ambercore (139504-68-0)	Ambercore (139504-68-0)	
LD50 dermal rat	> 2000 mg/kg	
Phenylethyl alcohol (60-12-8)		
LD50 oral rat	1609 mg/kg	
LD50 oral	1610 mg/kg bodyweight	
LD50 dermal rabbit	2535 mg/kg	
LD50 dermal	2500 mg/kg bodyweight	
LC50 Inhalation - Rat	> 4.63 mg/l/4h	

Version: 1

Ethylene brassylate (105-95-3)		
LD50 oral rat		> 5000 mg/kg
LD50 dermal rabbit		> 5000 mg/kg
Ethyl vanillin (121-32-4)		
LD50 oral rat		1590 mg/kg
LD50 oral		3000 mg/kg bodyweight
LD50 dermal rat		> 2000 mg/kg
Cinnamic alcohol (104-54-1)		
LD50 oral		2000 mg/kg bodyweight
LD50 dermal rabbit		> 5000 mg/kg
beta-lonone (14901-07-6)		
LD50 oral rat		4590 mg/kg
LD50 oral		3490 mg/kg bodyweight
Isopropyl quinoline (135-79-5)		
LD50 oral		1500 mg/kg bodyweight
LD50 dermal		160 mg/kg bodyweight
Benzaldehyde (100-52-7)	<u>'</u>	
LD50 oral rat		1292 mg/kg
LD50 dermal rabbit		> 1250 mg/kg
Skin corrosion/irritation		Causes skin irritation.
Serious eye damage/irritation		Causes serious eye irritation.
Respiratory or skin sensitisation		May cause an allergic skin reaction.
Germ cell mutagenicity		Not classified
Carcinogenicity		Not classified
Reproductive toxicity		Not classified
STOT-single exposure		Not classified
STOT-repeated exposure		Not classified
Aspiration hazard	: 1	Not classified

# 11.2. Information on other hazards

No additional information available

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term : Not classified

(acute)

Hazardous to the aquatic environment, long–term : Very toxic to aquatic life with long lasting effects.

(chronic)

(CITIOTIIO)	
Hexamethylindanopyran (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 μg/l REACH Dossier

Version: 1

Hexamethylindanopyran (1222-05-5)		
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier	
Dipropylene glycol monomethyl ether (34590	-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Vertenex (32210-23-4)		
LC50 - Fish [1]	8.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])	
Methyl ionone (mixture of isomers) (1335-46-	2)	
LC50 - Fish [1]	2.3 mg/l (Exposure time: 96 h - Species: Danio rerio [static])	
Phenylethyl alcohol (60-12-8)		
EC50 - Crustacea [1]	287.17 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	490 mg/l (Species: Desmodesmus subspicatus)	
Ethyl vanillin (121-32-4)		
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
Benzaldehyde (100-52-7)		
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	

# 12.2. Persistence and degradability

Amberwood F (58567-11-6)	
Persistence and degradability	May cause long-term adverse effects in the environment.

# 12.3. Bioaccumulative potential

Hexamethylindanopyran (1222-05-5)		
BCF - Fish [1]	(1618 dimensionless (whole body w.w.)	
Partition coefficient n-octanol/water (Log Pow)	5.3 (at 25 °C (at pH 7)	
Dipropylene glycol monomethyl ether (34590-94-8)		
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	
Vertenex (32210-23-4)		
Partition coefficient n-octanol/water (Log Pow)	4.8 (at 25 °C)	
Methyl ionone (mixture of isomers) (1335-46-2)		
Partition coefficient n-octanol/water (Log Pow)	(>4.5 - <5 - at 23 °C (at pH 6.2)	
Amberwood F (58567-11-6)		
BCF - Fish [1]	(530 dimensionless (whole body w.w.)	
Partition coefficient n-octanol/water (Log Pow)	5.4 (at 25 °C)	
Bioaccumulative potential	Not established.	
Ambercore (139504-68-0)		
BCF - Fish [1]	(173 dimensionless)	

14

Issue Date: 24/04/2023

Version: 1

Phenylethyl alcohol (60-12-8)		
Partition coefficient n-octanol/water (Log Pow)	1.36 (at 20 °C (at pH 7)	
Ethylene brassylate (105-95-3)		
Partition coefficient n-octanol/water (Log Pow)	4.3 (at 25 °C (at pH 6.4-7)	
Ethyl vanillin (121-32-4)		
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)	
Cinnamic alcohol (104-54-1)		
Partition coefficient n-octanol/water (Log Pow)	1.636 (at 27 °C (at pH 3.52)	
beta-lonone (14901-07-6)		
Partition coefficient n-octanol/water (Log Pow)	1.903 (at 27 °C (at pH 5.7)	
beta-Caryophyllene (87-44-5)		
Partition coefficient n-octanol/water (Log Pow)	6.23 (at 25 °C (at pH 7)	
Benzaldehyde (100-52-7)		
BCF - Fish [1]	(no significant bioaccumulation)	
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)	

## 12.4. Mobility in soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

No additional information available

# 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082

15

Issue Date: 24/04/2023

Version: 1

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shippin	14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER)
Transport document descr	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (ISO E SUPER), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9,	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO E SUPER), 9,
14.3. Transport hazard	class(es)			
9	9	9	9	9
9	•		9	•
14.4. Packing group	14.4. Packing group			
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

# 14.6. Special precautions for user

# **Overland transport**

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 51 Excepted quantities (ADR) : E1

: P001, IBC03, LP01, R001 Packing instructions (ADR)

Special packing provisions (ADR) : PP1 Mixed packing provisions (ADR) : MP19 Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions : TP1, TP29 (ADR)

: LGBV Tank code (ADR) Vehicle for tank carriage : AT Transport category (ADR) : 3 : V12 Special provisions for carriage - Packages (ADR) Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates

Tunnel restriction code (ADR)

EAC code : •3Z

Version: 1

#### Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 : LP01, P001 Packing instructions (IMDG) : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC03 : T4 Tank instructions (IMDG) : TP1, TP29 Tank special provisions (IMDG) : F-A EmS-No. (Fire) EmS-No. (Spillage) : S-F Stowage category (IMDG) : A

#### Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

### Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

#### Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Version: 1

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	OLIVIANDERS; Iso E Super; Vertenex; Methyl ionone (mixture of isomers); Amberwood F; Patchouli oil; Phenylethyl alcohol; Bacdanol; Isopropyl quinoline; Benzaldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	OLIVIANDERS; Iso E Super; Hexamethylindanopyran; Methyl ionone (mixture of isomers); Amberwood F; Patchouli oil; Ambercore; Bacdanol; Ethylene brassylate; beta-lonone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

## **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

# POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

## Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

## Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

## Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Version: 1

#### 15.1.2. National regulations

#### France

#### Occupational diseases

Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

#### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).

Observe restrictions according Act on the Protection of Young People in Employment

(JArbSchG).

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen SZW-lijst van reprotoxische stoffen – Borstvoeding

SZW-lijst van reprotoxische stoffen – Borstvoedin

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

: None of the components are listed: None of the components are listed

: None of the components are listed

: None of the components are listed

: None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.

19

Issue Date: 24/04/2023

Version: 1

Full text of H- and EUH-statements:	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.